

RTB Phoenix air to water heat pump 5.5kW:  
RTB Phoenix luft til vand varmepumpe 5,5kW:

## DATASHEET/DATABLAD



# DATASHEET/DATABLAD

DK	UK	Værdi/Value
<b>INTELLIGENT INVERTER VARMEPUMPE</b>	<b>INTELLIGENT INVERTER HEAT PUMP</b>	
MODEL	MODEL	P6
NOMINEL SPÆNDING/FREKVENNS	RATED VOLTAGE/FREQUENCY	220-240V— /50Hz
FUGTRESISTENS	MOISTURE RESISTANCE	IPX4
ELEKTRISK STØDSIKKERHED	ELECTRICAL SHOCKPROOF	I
OPVARMNINGSKAPACITET (A)	HEATING CAPACITY( A)	2.290-8.250kW
VARMEEFFEKT-INPUT (A)	HEATING POWER INPUT (A)	0.630-1.810kW
KØLEKAPACITET (B)	COOLING CAPACITY (B)	1 980-6.100kW
KØLEEFFEKT-INPUT (B)	COOLING POWER INPUT (B)	0.700-2.220kW
VARMTVANDSKAPACITET (C)	HOT WATER CAPACITY(C)	3.000-9.770kW
VARMT VAND STRØM-INPUT (C)	HOT WATER POWER INPUT (C)	0.600-2 350kW
*NOMINEL EFFEKT-INPUT	*RATED POWER INPUT	2.900kW
*NOMINEL STRØM-INPUT	*RATED CURRENT INPUT	13.0A
VANDPUMPE EFFEKT-INPUT	WATER PUMP POWER INPUT	52W
VANDHØJDE	WATER HEAD	5.5m
VANDFLOWVOLUMEN	WATER FLOW VOLUME	1.0 m3/h
KØLEMIDDEL/KORREKT INPUT	REFRIGERANT/ PROPER INPUT	R32/1.3kg
STØJ	NOISE	37-54dB(A)
NETTOVÆGT	NET WEIGHT	90kg
DRIFTSTRYK (LAVE SIDE)	OPERATION PRESSURE(LOW SIDE)	2.1 MPa
DRIFTSTRYK (HØJE SIDE)	OPERATION PRESSURE(HIGHT SIDE)	4.4MPa
MAKSIMALT TILLADT TRYK	MAXIMUM ALLOWABLE PRESSURE	4.4MPa
FABRIKSNUMMER (PÅ STREGKODEN)	FACTORY NUMBER(ON THE BAR CODE)	
PRODUKTIONS DATO (PÅ STREGKODEN)	MANUFACTURED DATE(ON THE BAR CODE)	
A: OMGIVELSESTEMP. (DB/WB 7°C/6°C), VANDTMP. (IND/UD): 30°C/35°C	A: AMBIENT TEMP.(DB/WB 7°C/6°C, WATER TEMP.(IN/OUT):30°C/35°C	
B: OMGIVELSESTEMP. (DB/WB) 35°C/24°C, VANDTMP. (IND/UD): 12°C/7°C	B: AMBIENT TEMP (DB/WB) 35°C/24°C, WATER TEMP.(IN/OUT):12°C/7°C	
C: OMGIVELSESTEMP. (DB/WB): 20°C/15°C, VANDTMP. (UD): CIRKULATION FRA 15°C TIL 55°C	C: AMBIENT TEMP.(DB/WB): 20°C/15°C, WATER OUTLET TEMPERATURE CIRCULATION FROM 15°C TO 55°C	

\* I henhold til IEC/EN 60335-1 \*According to IEC/EN 60335-1

