

RTB Phoenix air to water heat pump 14kW:  
RTB Phoenix luft til vand varmepumpe 14kW:

DATASHEET/DATABLAD



# DATASHEET/DATABLAD

DK	UK	Værdi/Value
<b>INTELLIGENT INVERTER VARMEPUMPE</b>	<b>INTELLIGENT INVERTER HEAT PUMP</b>	
MODEL	MODEL	P17T
NOMINEL SPÆNDING/FREKVENNS	RATED VOLTAGE/FREQUENCY	380-415V/3N-/50Hz
FUGTRESISTENS	MOISTURE RESISITANCE	IPX4
ELEKTRISK STØDSIKKERHED	ELECTRICAL SHOCKPROOF	I
OPVARMNINGSKAPACITET (A)	HEATING CAPACITY( A)	7.000-20.50kW
VARMEEFFEKT-INPUT (A)	HEATING POWER INPUT (A)	1.500-6.000kW
KØLEKAPACITET (B)	COOLING CAPACITY (B)	5.500-15.50kW
KØLEEFFEKT-INPUT (B)	COOLING POWER INPUT (B)	1.500-6.000kW
VARMTVANDSKAPACITET (C)	HOT WATER CAPACITY(C)	9.350-24.30kW
VARMT VAND STRØM-INPUT (C)	HOT WATER POWER INPUT (C)	2.060-6.400kW
*NOMINEL EFFEKT-INPUT	*RATED POWER INPUT	7.200kW
*NOMINEL STRØM-INPUT	*RATED CURRENT INPUT	12.0A
VANDPUMPE EFFEKT-INPUT	WATER PUMP POWER INPUT	180W
VANDHØJDE	WATER HEAD	12.5m
VANDFLOWVOLUMEN	WATER FLOW VOLUME	2.9m <sup>3</sup> /h
KØLEMIDDEL/KORREKT INPUT	REFRIGERANT/ PROPER INPUT	R32/2.0kg
STØJ	NOISE	44-58dB(A)
NETTOVÆGT	NET WEIGHT	157kg
DRIFTSTRYK (LAVE SIDE)	OPERATION PRESSURE(LOW SIDE)	2.1MPa
DRIFTSTRYK (HØJE SIDE)	OPERATION PRESSURE(HIGHT SIDE)	4.4MPa
MAKSIMALT TILLADT TRYK	MAXIMUM ALLOWABLE PRESSURE	4.4MPa
FABRIKSNUMMER (PÅ STREGKODEN)	FACTORY NUMBER(ON THE BAR CODE)	
PRODUKTIONSDATO (PÅ STREGKODEN)	MANUFACTURED DATE(ON THE BAR CODE)	
A: OMGIVELSESTEMPERATUR (DB/WB) 7°C/6°C, VANDTEMP. (IND/UD): 30°C/35°C	A: AMBIENT TEMP.(DB/WB) 7°C/6°C,WATER TEMP.(IN/OUT):30°C/35°C	
B: OMGIVELSESTEMPERATUR (DB/WB) 35°C/24°C, VANDTEMP. (IND/UD): 12°C/7°C	B: AMBIENT TEMP.(DB/WB) 35°C/24°C,WATER TEMP(IN/OUT):12°C/7°C	
C: OMGIVELSESTEMPERATUR (DB/WB) 20°C/15°C, VANDUDLØBSTEMPERATUR CIRKULATION FRA 15°C TIL 55°C	C: AMBIENT TEMP.(DB/WB) 20°C/15°C, WATER OUTLET TEMPERATURE CIRCULATION FROM 15°C TO 55°C	

\* I henhold til IEC/EN 60335-1    \*According to IEC/EN 60335-1

