

RTB Phoenix air to water heat pump 20kW:
RTB Phoenix luft til vand varmepumpe 20kW:

DATASHEET/DATABLAD



DATASHEET/DATABLAD

DK	UK	Værdi/Value
INTELLIGENT INVERTER VARMEPUMPE	INTELLIGENT INVERTER HEAT PUMP	
MODEL	MODEL	P24T
NOMINEL SPÆNDING/FREKVENNS	RATED VOLTAGE/FREQUENCY	380-415V/3N-50Hz
FUGTRESISTENS	MOISTURE RESISITANCE	IPX4
ELEKTRISK STØDSIKKERHED	ELECTRICAL SHOCKPROOF	I
OPVARMNINGSKAPACITET (A)	HEATING CAPACITY(A)	10.00-25.00kW
VARMEEFFEKT-INPUT (A)	HEATING POWER INPUT (A)	2.800-5.700kW
KØLEKAPACITET (B)	COOLING CAPACITY (B)	6.400-15.80kW
KØLEEFFEKT-INPUT (B)	COOLING POWER INPUT (B)	3.400-6.800kW
VARMTVANDSKAPACITET (C)	HOT WATER CAPACITY(C)	14.30-28.10kW
VARMT VAND STRØM-INPUT (C)	HOT WATER POWER INPUT (C)	3.400-7.000kW
*NOMINEL EFFEKT-INPUT	*RATED POWER INPUT	12.80kW
*NOMINEL STRØM-INPUT	*RATED CURRENT INPUT	20.5A
VANDPUMPE EFFEKT-INPUT	WATER PUMP POWER INPUT	500W
VANDHØJDE	WATER HEAD	21m
VANDFLOWVOLUMEN	WATER FLOW VOLUME	4.2m3/h
KØLEMIDDEL/KORREKT INPUT	REFRIGERANT/ PROPER INPUT	R32/3.4kg
STØJ	NOISE	53-59dB(A)
NETTOVÆGT	NET WEIGHT	206kg
DRIFTSTRYK (LAVE SIDE)	OPERATION PRESSURE(LOW SIDE)	2.1MPa
DRIFTSTRYK (HØJE SIDE)	OPERATION PRESSURE(HIGHT SIDE)	4.4MPa
MAKSIMALT TILLADT TRYK	MAXIMUM ALLOWABLE PRESSURE	4.4MPa
FABRIKSNUMMER (PÅ STREGKODEN)	FACTORY NUMBER(ON THE BAR CODE)	
PRODUKTIONSDATO (PÅ STREGKODEN)	MANUFACTURED DATE(ON THE BAR CODE)	
A: OMGIVELSESTEMP. (DB/WB 7°C/6°C), VANDTMP. (IND/UD): 30°C/35°C	A: AMBIENT TEMP.(DB/WB): 7°C/6°C,WATER TEMP.(IN/OUT):30°C/35°C	
B: OMGIVELSESTEMP. (DB/WB) 35°C/24°C, VANDTMP. (IND/UD): 12°C/7°C	B. AMBIENT TEMP (DB/WB) 35T/24T,WATER TEMP (IN/OUT):12°C/7°C	
C: OMGIVELSESTEMP. (DB/WB): 20°C/15°C, VANDTMP. (UD): CIRKULATION FRA 15°C TIL 55°C	C: AMBIENT TEMP.(DB/WB): 20°C115°C, WATER OUTLET TEMPERATURE CIRCULATION FROM 15°C TO 55°C	

* I henhold til IEC/EN 60335-1 *According to IEC/EN 60335-1

